







# Plastic Belting Options

## Standard 8" Profile



DYNAMIC CONVEYOR  
CORPORATION








Description	Options	Functions / Features / Construction
Standard Flat Top Belt 	Polypropylene	<ul style="list-style-type: none"> <li>Belt is captured in tracks along belt guides in side walls of conveyor</li> <li>3' of belting is required for each 17-1/2" Straight Module and Drive Module</li> <li>1' of belting is required for each 6-1/2" connector module (angle or straight)</li> <li>4' of belting is required for the Feed End Module</li> </ul>
Standard Flat Top Drive Flights 	1" Height 2" Height 3" Height 1/2" to 2-1/2" heights available	<ul style="list-style-type: none"> <li>Interlaced in the belt to carry product along an inclining and/or declining angle</li> <li>Installed at customer specified intervals along the belt (exact spacing must be specified)</li> <li>Standard flight indented .7" (.4" flight indent available on request)</li> <li>Constructed of grey polypropylene</li> </ul>
Rubber Flat Top Drive Flights 	1" Height 2" Height	<ul style="list-style-type: none"> <li>Interlaced in the belt to carry product along an inclining and/or declining angle</li> <li>Installed at customer specified intervals along the belt (exact spacing must be specified)</li> <li>Flight indented .7"</li> <li>Constructed of grey rubber</li> </ul>
Flush Grid Belt 	Polypropylene Acetal	<ul style="list-style-type: none"> <li>Use for water bath, wash down and cooling applications</li> <li>38% open area</li> </ul>
Perforated Flat Top Belt 	Polypropylene Polyethylene Acetal Nylon	<ul style="list-style-type: none"> <li>Use for water bath, wash down and cooling applications</li> <li>Use for finger separator applications</li> <li>6.4% open area</li> </ul>
Mesh Top Belt 	Polypropylene	<ul style="list-style-type: none"> <li>Use for water bath, wash down and cooling applications</li> <li>24% open area</li> </ul>

# Plastic Belting Options

## Standard 8" Profile



DYNAMIC CONVEYOR  
CORPORATION

Description	Options	Functions / Features / Construction
Flat Friction Top Belt 	Black Santoprene	<ul style="list-style-type: none"> <li>• Use for "soft drop" of highly cosmetic product</li> <li>• Black santoprene has a Shore A durometer 45</li> <li>• White santoprene has a Shore A durometer 56</li> </ul>
Diamond Friction Top Belt 	Black Santoprene	<ul style="list-style-type: none"> <li>• Use for "soft drop" of highly cosmetic product</li> <li>• Black santoprene has a Shore A durometer 45</li> <li>• White santoprene has a Shore A durometer 56</li> </ul>
Nylon Flat Top Belt 	Dark Brown Nylon	<ul style="list-style-type: none"> <li>• Use in high temperature applications</li> </ul>
Flush Grid Belt with Roller Inserts 	Polypropylene with Acetal rollers	<ul style="list-style-type: none"> <li>• Use for low back pressure accumulation</li> <li>• Use for delicate package conveyance</li> <li>• For use on horizontal conveyors only</li> <li>• 38% open area</li> </ul>
Radius Flush Grid Belt 	Polypropylene Acetal	<ul style="list-style-type: none"> <li>• Use for radius turn applications</li> <li>• 42% open area</li> </ul>
Radius Flat Friction Flush Grid Belt 	Grey Santoprene	<ul style="list-style-type: none"> <li>• Use for radius turn applications</li> <li>• Use for "soft drop" of highly cosmetic product</li> <li>• 42% open area</li> <li>• Grey santoprene has a Shore A durometer 56</li> </ul>
Radius Drive Flights 	1" Height 2" Height 3" Height  1/2" to 2-1/2" heights available	<ul style="list-style-type: none"> <li>• Use for radius turn applications</li> <li>• 42% open area</li> <li>• Constructed of polypropylene or acetal</li> </ul>