







Drive & Feed End Modules

Standard 8" Profile



**DYNAMIC CONVEYOR
CORPORATION**

Fill in __ with 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 36, 42, 48, 54 or 60
for conveyor width

Drive Modules	Options	Ref. Number	Functions / Features / Construction
External Mount Motor and Control 	Variable Speed 1/2 - 26 FPM 1 - 47 FPM 2 - 78 FPM	HDV__ E Specific part number will be configured during the quoting phase.	<ul style="list-style-type: none"> Available for all widths 110 VAC single phase, 230 VAC single phase or 230 three phase Lockable speed control Brushless Stainless steel shaft Required for water applications Requires 3' of belt
Internal Mount Motor 	Variable Speed 1/2 - 26 FPM 1 - 47 FPM 2 - 78 FPM	HDV__ I Specific part number will be configured during the quoting phase.	<ul style="list-style-type: none"> Available for widths 10" or more 110 VAC single phase, 230 VAC single phase or 230 three phase Lockable speed control Brushless Stainless steel shaft Required for water applications Requires 3' of belt
External Mount AC Variable Frequency Motor 	Variable Speed 1/8HP - 11 FPM 1/4HP - 35 FPM 1/2HP - 70 FPM	HDV__ EVFD Specific part number will be configured during the quoting phase.	<ul style="list-style-type: none"> Available for all widths 110/60/1ph, 230/60/1ph or 460/60/3ph 500 in lb/155 torque Brushless Stainless steel shaft Requires 3' of belt
External Mount Radius Turn Motor 	Variable Speed 1/8HP - 11 FPM 1/4HP - 35 FPM 1/2HP - 70 FPM	RTVS__ E Specific part number will be configured during the quoting phase.	<ul style="list-style-type: none"> Available for radius turn conveyors Brushless Stainless steel shaft Requires 3' belt Indexing and reversing options not available
Feed End Modules	Options	Part Number	Functions / Features / Construction
Feed End Module 		TENX__	<ul style="list-style-type: none"> Begins the return end of a conveyor system Required in all systems Requires 4' of belt
Heavy Duty Feed End Module 		TENX__-HD	<ul style="list-style-type: none"> Typically used on conveyors that require more than 100 square feet of belting External adjustment mechanism Requires 4' of belt