


Mid Modules & Connectors

Standard 8" Profile



Fill in __ with 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 36, 42, 48, 54 or 60 for conveyor width

DYNAMIC CONVEYOR CORPORATION

Modules / Connectors	Part Number	Functions / Features / Construction
17-1/2" Straight Extension 	EDNX__	- Connect between feed and drive modules to extend by 17-1/2" - Requires 3' of belt
6-1/2" Straight Connector 	JSNX__	- A straight connector will connect with another straight, 30° or 45° angle - Requires 1' of belt
30° Angle Connector 	JTNX__	- Use angles to change elevation (ascending or descending) - Use a combination of angle connectors to achieve angles of various degrees - Requires 1' of belt
45° Angle Connector 	JFNX__	- Use angles to change elevation (ascending or descending) - Use a combination of angle connectors to achieve angles of various degrees - Requires 1' of belt
Standard Radius Turn Modules 	R__45 R__60 R__90	- Standard profile height (8") - Available in 4" - 24" widths - Available in 45°, 60°, and 90° radius turns - Connect between two modules to allow the conveyor to turn right or left at a given angle - Use with External Mount Radius Turn Drive Module - Requires Straight Extension Module(s) before changing direction (right or left) - Requires Series 2400 Radius Flush Grid Belt - Reversing options not available
Retaining Wall Kit for Radius Turn Modules	KITR__45 KITR__60 KITR__90	- Use when additional wall height is required - Adds 4" of height to existing 1-1/2" retaining wall - One kit required per module